

# SAFETY DATA SHEET

According to OSHA HCS 2012 (29 CFR 1910.1200)

## SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** Butane-Isobutane Mix  
**Other means of identification:** Commercial Butane, Mixed Butane  
**CAS Number:** 106-97-8  
**SDS Number:** OKE013  
**Product type:** Liquefied Petroleum Gas (LPG)  
**Identified uses:** Industrial Use



**Manufacturer:**  
ONEOK, Inc.  
100 W. Fifth Street  
Tulsa, OK 74103

**SDS Information:**  
Phone: (888) 417-6275  
Fax: (918) 588-7543  
URL: [www.oneok.com](http://www.oneok.com)

**Emergency Health and Safety Number:**  
Chemtrec: (800) 424-9300 (24 hours)

## SECTION 2: CHEMICAL HAZARDS IDENTIFICATION

**GHS Classification:** H220 - Flammable gases, Category 1  
H280 - Gases under pressure (Liquefied gas)

GHS Label Elements	
<b>Hazard Symbol(s):</b>	 
<b>Signal Word:</b>	Danger
<b>Hazard Statement(s):</b>	H220: Extremely flammable gas. H280: Contains gas under pressure; may explode if heated.
<b>Precautionary Statements:</b>	<b>Prevention</b> P210: Keep away from heat/sparks/open flames/ hot surfaces. - No smoking <b>Response:</b> P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381: Eliminate all ignition sources if safe to do so. <b>Storage:</b> P410+403: Protect from sunlight. Store in a well-ventilated place.
<b>Other Hazards:</b>	Simple asphyxiant - may displace oxygen and cause rapid suffocation. May form explosive mixtures with air. Contact with liquid may cause frost bite.

---

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

---

Chemical Name	CAS Number	% By Weight
n-Butane	106-97-8	68-74
Isobutane	75-28-5	18-30
Isopentane	78-78-4	0-6
Propane	74-98-6	0-2
Pentane	109-66-0	0-2
Ethane	74-84-0	0-0.5

All concentrations are percent by weight unless ingredient is a gas, gas concentrations are percent by volume. Data are typical values based on material tested, but may vary from sample to sample.

---

**SECTION 4: FIRST AID MEASURES**

---

**Eye Contact:**

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove contact lenses if present and easy to do. Continue to rinse for at least 15 minutes. Get medical attention if eye irritation persists.

**Inhalation:**

If irritation, headache, nausea, or drowsiness occurs, remove victim from the source of exposure and into fresh air. If breathing is difficult, oxygen should be administered by qualified personnel. Seek medical attention if respiratory irritation persists.

**Skin Contact:**

Wash skin with plenty of soap and water until no evidence of the chemical remains (at least 15 minutes). Liquefied gases may cause cryogenic burns, in case of cryogenic burn immediately place affected area in lukewarm water to slowly warm. DO NOT USE HOT WATER. Seek immediate medical attention.

**Ingestion:**

As this product is a gas under normal atmospheric conditions, ingestion is unlikely.

**Most Important Symptoms and Effects:**

**Acute:** Inhalation of oxygen-deficient atmospheres. Symptoms of oxygen deficiency include difficulty breathing, headache, dizziness, and nausea; at high concentrations, unconsciousness or death may occur. Contact with the liquefied or pressurized gas may cause frostbite (cold burn).

**Delayed:** None known, Refer to Section 11 – Toxicological Information

**Notes to Physician:**

May sensitize the heart to epinephrine or other circulating catecholamines so that arrhythmias may occur. Careful consideration is essential preceding administration of epinephrine, cardiac stimulants or other treatment. If sympathomimetic are administered, observe for the development of cardiac arrhythmias.

---

## SECTION 5: FIRE-FIGHTING MEASURES

---



NFPA Hazard Class:  
Health – 1  
Fire – 4  
Reactivity – 0  
Specific Hazard – N/A

### Extinguishing Media:

Carbon dioxide or dry chemical is the recommended media. Flood large fires with fine water spray.

### Specific Hazards arising from the chemical:

Severe explosion and fire hazard. Contents under pressure, so containers may rupture or explode if exposed to heat. Vapor/air mixtures are explosive. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back.

### Thermal Decomposition Products or Combustion:

Oxides of carbon, and oxides of nitrogen.

### Special Protective Actions for Fire-Fighters:

Move container from fire area if it can be done without risk. Cool containers from a safe distance with water spray until well after the fire is out. Stay away from ends of tanks. Keep unnecessary people away, isolate hazard area and deny entry. Withdraw immediately in case of rising sound from venting safety device. Do not attempt to extinguish fire unless flow of material can be stopped first. Be aware that a BLEVE (Boiling Liquid Expanding Vapor Explosion) may occur unless surfaces are kept cool with water. Apply water from a protected location or from a safe distance. Stay upwind and keep out of low areas. Evacuate if fire gets out of control or containers are directly exposed to fire.

### Special Protective Equipment for Fire-Fighters:

Emergency responders should wear proper protective equipment and a positive pressure self-contained breathing apparatus.

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

### Personal Precautions, Protective Equipment and Emergency Procedures:

Extremely flammable; Avoid heat, flames, sparks, and other sources of ignition. Spills of liquids can create a fire hazard and may form an explosive atmosphere. The vapor is heavier than air and can accumulate in low areas. Avoid breathing vapors, mist or gas. Stay upwind from release, and avoid direct contact. Ventilate closed spaces before entering. Notify persons downwind for large spills. Ventilate area and allow material to evaporate.

### Environmental Precautions:

Prevent further release if it can be done safely. Prevent material from entering sewers and drains. If the material contaminates waterways or drains then notify appropriate authorities.

**Methods and Material for Containment and Cleaning up:**

Contain spillage using spark-proof tools and explosion-proof equipment. Place in container for disposal according to local / national regulations.

---

**SECTION 7: HANDLING AND STORAGE**

---

**Precautions for Safe Handling:**

Ground/bond any equipment used in handling the material. Only use non-sparking tools; keep away from heat, sparks, open flame or any other ignition source. Do not allow eating, drinking, or smoking in the area. Provide adequate ventilation. Use only explosion-proof electrical (ventilation, lighting, etc.) equipment. Empty containers retain product residue and can be hazardous, do not puncture or incinerate container.

**Conditions for Safe Storage:**

Store in accordance with local regulations. Store in a segregated and approved area that is cool, dry, well-ventilated, and away from direct sunlight or any ignition sources. Keep container tightly closed and sealed. Store separate from any incompatible material (Section 10).

---

**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

Chemical Name	OSHA PEL (ppm)	ACGIH TLV (ppm)	Other
n-Butane	None	1000 (STEL)	800 ppm REL (NIOSH) Narcosis, Asphyxiant
Isobutane	None	1000 (STEL)	800 ppm REL (NIOSH) Narcosis, Asphyxiant
Isopentane	1000	1000	120 ppm REL (NIOSH) 1500 ppm IDLH (NIOSH)
Propane	1000	1000	1000 ppm REL (NIOSH) 2100 ppm IDLH (NIOSH) Asphyxiant
Pentane	1000	1000	120 ppm REL (NIOSH) 1500 ppm IDLH, Asphyxiant
Ethane	None	None	Asphyxiant

**Engineering Controls:**

General or local exhaust ventilation and other forms of engineering controls are the preferred means for keeping worker exposure to airborne contaminants below any recommended or statutory limits. If ventilation cannot reduce airborne concentrations below acceptable limits, appropriate respiratory protection should be used.

**Hygiene Measures:**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

**Eye/Face Protection:**

Safety eyewear (such as splash goggles) that meets ANSI Z.87.1 should be used to avoid exposure to liquid splashes, mists, gases, or dusts. Face shields may be necessary if contact is possible.

**Hand Protection:**

Chemical resistant, impervious gloves should be worn at all times when handling chemical products. Consider the parameters specified by the glove manufacturer, check that the gloves are still retaining their protective properties prior to use. Gloves should be discarded if there is any degradation or breakthrough.

**Body Protection:**

Wear flame retardant anti-static protective clothing. When there is a risk of liquid exposure, wear cold insulating clothing.

**Respiratory Protection:**

A NIOSH approved air purifying respirator with an appropriate cartridge or canister may be appropriate under certain conditions where airborne concentrations are expected to exceed exposure limits. Appropriate respirator selection should be made by a qualified professional as part of a comprehensive respiratory program as described in 29 CFR 1910.134. Protection provided by air-purifying respirators is limited and should not be used in atmospheres deficient in oxygen or where airborne concentrations are immediately dangerous to life or health. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

---

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

<b>Appearance:</b>	Colorless	<b>Flammability (Solid, gas):</b>	Extremely Flammable
<b>Physical Form:</b>	Liquefied Gas	<b>Upper Explosive Limit:</b>	8.4%
<b>Odor:</b>	Disagreeable	<b>Lower Explosive Limit:</b>	1.9%
<b>Odor Threshold:</b>	No Data	<b>Vapor Pressure:</b>	40.5-44.5 PSI@38°C
<b>pH:</b>	Not Applicable	<b>Vapor Density (air=1):</b>	2
<b>Melting Point:</b>	-216°F (-138°C)	<b>Viscosity:</b>	No Data
<b>Boiling Point:</b>		<b>Partition Coefficient (n-octanol/water):</b>	No Data
<b>Flash Point:</b>	-76°F (-60°C)	<b>Auto Ignition Temperature:</b>	761° F (405° C)
<b>Evaporation Rate:</b>		<b>Decomposition Temperature:</b>	No Data
<b>Solubility in Water:</b>	Slightly Soluble	<b>Volatile Percent:</b>	100%
<b>Solubility in Other Solvents:</b>	Hydrocarbons, alcohol, ether	<b>Specific Gravity (Water =1):</b>	0.579

---

**SECTION 10: STABILITY AND REACTIVITY**

---

<b>Reactivity:</b>	Stable at normal ambient temperatures and pressure
<b>Chemical Stability:</b>	Stable at normal ambient temperatures and pressure
<b>Possibility of Hazardous Reactions:</b>	Hazardous reactions are not anticipated



**Conditions to Avoid:** Avoid all possible sources of ignition. Containers may rupture or explode if exposed to heat.

**Incompatible Materials:** Avoid contact with acids and oxidizing materials.

**Hazardous Decomposition Products:** Oxides of carbon.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

### Information on Toxicological Effects:

#### Acute Toxicity:

Product Name	Result	Species	Dose	Exposure
Butane mix	Inhalation LC <sub>50</sub> , no data available			
Butane mix	Oral LD <sub>50</sub> , no available data			
Butane mix	Dermal LD <sub>50</sub> , no data available			
<b>Components</b>				
n-Pentane	Inhalation LC <sub>50</sub> (vapor) > 20,000 ppm	Rat (male)		4 hours

**Skin Irritation/Corrosion:** Contact with the liquefied or pressurized gas may cause frostbite (cold burn).

**Serious Eye Damage/Irritation:** Contact with the liquefied or pressurized gas may cause frostbite (cold burn).

**Sensitization:** Not expected to be a respiratory or skin sensitizer

**Mutagenicity:** Not expected to cause heritable genetic effects.

**Carcinogenicity:** Not expected to cause cancer. This substance is not listed as a carcinogen by IARC, NTP or OSHA.

**Reproductive Toxicity:** Not expected to cause reproductive toxicity.

**Developmental/Teratogenicity:** Not expected to cause developmental/teratogenicity effects.

**Specific Target Organ Toxicity (single exposure):** Not expected to cause effects on specific organs following a single exposure.

**Specific Target Organ Toxicity (repeated exposure):** Not expected to cause effects on specific organs following repeated exposures.

**Aspiration Hazard:** Not applicable.



**Information on the Likely Routes of Exposure:**

**Potential Acute Health Effects:**

- Eye Contact:** Contact with liquefied or pressurized gas may cause burns similar to frostbite.
- Inhalation:** Unlikely to be harmful. High concentrations in confined spaces may limit oxygen available for breathing.
- Skin Contact:** Dermal contact with liquefied or pressurized gas may cause burns similar to frostbite.
- Ingestion:** Ingestion of liquefied or pressurized gas may cause burns similar to frostbite.

**Symptoms related the Physical, Chemical and Toxicological Characteristics:** At high concentrations, simple asphyxiants can cause narcotic effects. Symptoms of overexposure may include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting. Eye contact, skin contact, or ingestion may cause burns similar to frostbite.

**Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure:** There are no known acute or chronic effects.

**Potential Chronic Health Effects:**

- General:** There are no known effects
- Carcinogenicity:** There are no known effects
- Mutagenicity:** There are no known effects
- Teratogenicity:** There are no known effects
- Developmental Effects:** There are no known effects
- Fertility Effects:** There are no known effects

**Numerical Measures of Toxicity:**

**Acute Toxicity Estimates:** Not available

**Component Toxicology:**

**Mutagenicity :**

Component	Type of Study	In Vitro/In Vivo	Metabolic Activation	Result
n-Butane	Chromosome Aberration	In Vitro	With and without	Negative
n-Butane	Ames Test	In Vitro	With and Without	Negative
n-Butane	Drosophila Sex Linked Recessive Lethal Assay	In Vivo	Not Applicable	Negative
Isobutane	Ames Test	In Vitro	With and Without	Negative
Propane	Ames Test	In Vitro	With and Without	Negative
Isopentane	Ames Test	In Vitro	With and Without	Negative



**Repeated Dose (Inhalation):**

**n-Butane (106-97-8):** No systemic toxicity or neurological effects were observed in male or female rats exposed to 0, 900, 3,000, or 9,000 ppm n-butane 6 hours/day, 7 days/week for 28 days. A NOAEC of 9,000 ppm was determined for systemic effects based on this study.

**Isobutane (75-28-5):** No systemic toxicity or neurological effects were observed in male or female rats exposed to 0, 900, 3,000, or 9,000 ppm isobutane 6 hours/day, 7 days/week for up to 6 weeks. A NOAEC of 9,000 ppm was determined for systemic effects based on this study.

**Propane (74-98-6):** Male and female rats were exposed to 0, 1,200, 4,000, or 12,000 ppm propane 6 hours/day, 7 days/week up to six weeks. For this study, the NOAEC for male rats was 4,000 ppm based on reduced bodyweight gain at 12,000 ppm during the first week and the NOAEC for female rats was 12,000 ppm (no effects were observed).

**Ethane (74-84-0):** No systemic toxicity or neurological effects were observed in male or female rats exposed to 0, 1,600, 5,000, or 16,000 ppm ethane 6 hours/day, 7 days/week up to six weeks. Based on this study, a no observed adverse effect concentration (NOAEC) of 16,000 ppm was determined for systemic effects.

**Reproductive/Developmental Toxicity (Inhalation):**

**n-Butane (106-97-8):** No adverse effects on mating, fertility, gestational indices or reproductive performance were observed in male or female rats exposed to 0, 900, 3,000, or 9,000 ppm n-butane 6 hours/day, 7 days/week for up to 6 weeks prior to, during, and after mating. Based on this study a NOAEC of 9000 ppm was determined.

**Isobutane (75-28-5):** No adverse effects on mating, fertility, gestational indices or reproductive performance were observed in male or female rats exposed to 0, 900, 3,000, or 9,000 ppm n-butane 6 hours/day, 7 days/week for up to 6 weeks prior to, during, and after mating. Based on this study a NOAEC of 9000 ppm was determined.

**Propane (74-98-6):** Male and female rats were exposed to 0, 1,200, 4,000, or 12,000 ppm propane 6 hours/day, 7 days/week up to six weeks prior to, during, and after mating. There were no effects on fertility or reproductive performance, including offspring survival and weight development up to post-natal day 4. A NOAEC of 12,000 ppm was determined for fertility, reproductive, and developmental endpoints in this study.

**Ethane (74-84-0):** No adverse effects on mating, fertility, gestational indices or reproductive performance were observed in male or female rats exposed to 0, 1,600, 5,000, or 16,000 ppm ethane 6 hours/day, 7 days/week for up to 6 weeks prior to, during, and after mating. Based on this study a NOAEC of 16,000 ppm was determined.

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

<b>Toxicity:</b>	No data available. Gases will evaporate from the surface and will not be have significant adverse effects in the aquatic environment.
<b>Persistence and Degradation:</b>	No data available
<b>Bioaccumulative Potential:</b>	No data available
<b>Mobility in Soil:</b>	Gases will evaporate and should not be mobile in soil
<b>Other Adverse Effects:</b>	No known significant effects





---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

This material is a liquefied gas and would not typically be managed as a waste. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

---

**SECTION 14: TRANSPORT INFORMATION**

---

**Proper Shipping Name:** Petroleum Gases, Liquefied  
**UN Number:** UN1075  
**Hazard Class:** 2.1  
**Packing Group:** N/A  
**Marine Pollutant:**

---

**SECTION 15: REGULATORY INFORMATION**

---

**OSHA Hazard Communication Standard:**

This material is considered hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200.

**US Federal Regulations:**

**United States Inventory (TSCA 8b):** All components are listed or exempted.

**Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):** Components not listed

**Clean Air Act Section 112(r) for Accidental Release Prevention:**

**Ingredients:** Isobutane (75-28-5)  
Butane (106-97-8)  
Propane (74-98-6)  
Isopentane (78-78-4)  
n-Pentane (109-66-0)  
Ethane (74-84-0)

**Clean Air Act Section 602 Class I Substances:** Components not listed

**Clean Air Act Section 602 Class II Substances:** Components not listed

**DEA List I Chemicals (Precursor Chemicals):** Components not listed

**SARA 302/304:** No products were found for composition/information on ingredients.

**SARA 304 RQ:** Not Applicable

**SARA 311/312 Classification:** Fire hazard; sudden release of pressure.



**Composition/Information on Ingredients:**

Name	%	Fire Hazard	Sudden Release of Pressure	Reactive	Immediate (acute) Health Hazard	Delayed (chronic) Health Hazard
n-Butane	67-74	Yes	Yes	No	No	No
Isobutane	18-30	Yes	Yes	No	No	No
Isopentane	0-6	Yes	Yes	No	Yes	No
Propane	0-2	Yes	Yes	No	No	No
Pentane	0-2	Yes	Yes	No	Yes	No
Ethane	0-0.5	Yes	Yes	No	No	No

**SARA 313:** No products were found

**State Regulations:**

**Massachusetts Right to Know:** Isobutane (75-28-5)

- Butane (106-97-8)
- Propane (74-98-6)
- Isopentane (78-78-4)
- n-Pentane (109-66-0)
- Ethane (74-84-0)

**New York Right to Know Hazardous Substance List:**

- Ingredients:** Isobutane (75-28-5)  
Butane (106-97-8)  
Propane (74-98-6)  
Isopentane (78-78-4)  
n-Pentane (109-66-0)  
Ethane (74-84-0)

**New Jersey Right to Know Hazardous Substance List:**

- Ingredients:** Isobutane (75-28-5)  
Butane (106-97-8)  
Propane (74-98-6)  
Isopentane (78-78-4)  
n-Pentane (109-66-0)  
Ethane (74-84-0)

**Pennsylvania Right to Know Hazardous Substance List:**

- Ingredients:** Isobutane (75-28-5)  
Butane (106-97-8)  
Propane (74-98-6)  
Isopentane (78-78-4)  
n-Pentane (109-66-0)  
Ethane (74-84-0)



**California Proposition 65:**

Ingredients in this product are not regulated. This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

---

**SECTION 16: OTHER INFORMATION**

---

**HMIS Hazard Rating:**

Health – 1

Flammability – 4

Physical Hazard – 0

Personal Protection – N/A

**ACRONYMS**

ACGIH	American Conference of Governmental Industrial Hygienists	NIOSH	National Institute of Occupational Safety and Health
ANSI	American National Standards Institute	NTP	National Toxicology Program
CAS	Chemical Abstract Service	OSHA	Occupational Safety & Health Administration
CFR	Code of Federal Regulations	PEL	Permissible Exposure Limit
DEA	Drug Enforcement Administration	REL	Recommended Exposure Limit
GHS	Globally Harmonized System of Classification and Labeling of Chemicals	RQ	Reportable Quantity
HMIS	Hazardous Materials Information System	SARA	Superfund Amendments and Reauthorization Act of 1986 Title III
IDLH	Immediately Dangerous to Life and Health	SDS	Safety Data Sheet
LC <sub>50</sub>	Lethal concentration 50	STEL	Short Term Exposure Limit
LD <sub>50</sub>	Lethal Dose 50	TLV	Threshold Limit Value
IARC	International Agency For Research On Cancer	TSCA	Toxic Substances Control Act
NFPA	National Fire Protection Association	TWA	Time Weighted Average
NOAEC	No Observed Adverse Effect Concentration	US	United States

To the best of our knowledge, the information contained herein is accurate. However, neither ONEOK, Inc. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.